

DCMTK - Feature #213

Buffer overflows vermeiden

2004-04-07 00:00 - Jörg Riesmeier

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:	Marco Eichelberg	% Done:	100%
Category:		Estimated time:	0:00 hour
Target version:		Compiler:	
Module:	all		
Operating System:			
Description			
Z.B. snprintf() statt sprintf() verwenden, falls vorhanden. Dies sollte ab C99 der Fall sein.			
Ebenso OFStandard::strcpy() und OFStandard::strcat() statt strcpy() und strcat(), oder noch besser OFString verwenden (siehe auch Eintrag vom 2002-04-11).			
Es gibt auch einige Tools, die zur automatischen Ueberpruefung des Quelltextes eingesetzt werden koennen, z.B. http://www.dwheeler.com/bugfinder/ .			

History

#1 - 2018-06-29 15:29 - Marco Eichelberg

- Description updated
- % Done changed from 0 to 50

strcpy() and strcat() have been replaced by OFStandard::strcpy() and OFStandard::strcat() wherever possible in the public and private modules.

#2 - 2025-08-21 11:21 - Marco Eichelberg

- Status changed from New to Closed
- Assignee set to Marco Eichelberg
- % Done changed from 50 to 100

sprintf() has meanwhile been replaced by OFStandard::snprintf() wherever possible in the public and private modules.